



https://iqubx.com/aluminium-glass-doors/

Lock stile 145 X 40 Hinge stile & rails 92 X 40 Single / double glass 6mm - 10mm

POWDER COAT / ANODIZE





IQUBX Aluminium Glass Door GD01

IQUBX has launched a unique aluminium glass door GD01 which provides for an option of using single glass or double glass panels. These glass can be clear, frost finish or lacquered and may be float or toughened as per choice. A single glass panel of 6-10mm is recommended positioned in center of frame or optionally, $2 \cos 6-8$ mm glasses panels can be used for sleeker contemporary look and better acoustics.

The unique mouldings for fixing the glass have been designed so that they can be reversed to convert single pane door to double glass and vice-versa.

Another unique feature of IQUBX GD01 Aluminium glass door is integrated handle on both side of the main stile giving it a distinct aesthetics and functionality.

This aluminium door design scores in another way as glass panels can easily be changed without demounting the door from the door frame

These doors can be ordered in any colour of powder coating or anodizing to match the rest of interiors

GD01 aluminium glass door has been designed keeping in mind standard hardware available including concealed or open door closer, dead locks, mortise lock and optional handles (as GD01 comes with integrated handle in stile profile)

Technical Data

Main Lock Stile profile with integrated handle 138 x 40mm Main Lock Stile with moulding 145 x 40

Hinge stile and rails 80 x 40mm

Hinge stile and rails with moulding 92 x 40

Moulding 28 x 12

All components are raw mill finish and can be powder coated in any powder coat color or anodized

GREENPRO certified

6063 aluminium alloy, 100% recycled aluminium - 10% precosumer &~90% post-consumer



GD01 - integrated aesthetics with other IQUBX systems

This glass panel door, GD01 on hinges is ideal for use with IQUBX Aluminium modular door frame DF01, while it can be used with any other door frame too.

We recommend using GD01 / GD01S glass door with our Modular glass partition system GP2510, GP2512, GP2512D and GP1510 for a coordinated aesthetic interior. We also recommend using GD01 with our demountable partition system WP01P.

Key Features & Benefits

Single door for multiple glazing options like single & double glass

Handle is integrated within the section, giving a very clean aeesthetics

Glass panel can be changed without demounting the door

Double glass pane in the door will give enhanced acoustic insulation, especially when used with IQUBX DF01 door frame with double rubber seal

Greenpro certified by IGBC - suitable for green building certification of projects







https://iqubx.com/aluminium-glass-doors/

Lock & Hinge stile 145 X 40 Rails 92 X 40

POWDER COAT / ANODIZE

IQUBX Aluminium Sliding Glass Door GD01S

IQUBX GD01S is the sliding version of the versatile and unique GD01. It has all the features and benefits of the GD01 including muti glazing options and integrated handle.

The lock stile is used at both ends, giving it a very distinct aesthetics. Unique feature for better acoustic insulation is that door seals have been provisioned at both the stiles.

These doors can be ordered in any colour of powder coating or anodizing to match the rest of interiors

We recommend using GD01S glass door with our Modular glass partition system GP2510, GP2512, GP2512D and GP1510 for a coordinated aesthetic interior. We also recommend using GD01S with our demountable partition system WP01P.


GD01S aluminium glass door has been designed keeping in mind standard hardware available including soft closing sliding channel.

Technical Data

Stile profiles with integrated handle 138 x 40mm
Stiles with moulding 145 x 40
Rails 80 x 40mm
Rails with moulding 92 x 40
Moulding 28 x 12
All components are raw mill finish and can be powder coated in any powder coat color or anodized

GREENPRO certified 6063 aluminium alloy, 100% recycled aluminium - 10% precosumer & 90% post-consumer









https://iqubx.com/aluminium-glass-doors/

Lock stile 75 X 40.5 Hinge stile & rails 91/80 X 38.5 Single glass 8mm - 10mm

POWDER COAT / ANODIZE





IQUBX Aluminium Glass Door GD02 & sliding GD02S

GD02 is a very sleek single glass pane modular aluminum stile door suitable for all interior applications. GD02 can accommodate single glass pane of 8mm or 10mm.

The unique design of lock stile has provision for gasket in 2 places - on leading edge and adjacent face near the leading edge. Though G02 hinged door used with IQUBX DF01 door frame (which has double door seal) has superior acoustic insulation, this door can be used with any frame including wooden door frames with good acoustic insulation due to built in gasket provision. This gasket is also used for effective acoustic insulation in sliding configuration as GD02S. The first gasket in the leading edge is useful for floor machine application situation.

This aluminium door design also allows glass panels to be changed without demounting the door from the door frame. These doors can be ordered in any colour of powder coating or anodizing to match the rest of interiors.

We recommend using GD02 / GD02S glass doors with our Modular glass partition system GP2510, GP2512, GP2512D, GP18100 etc and demountable partition WP01P for a coordinated aesthetic interior.

GD02 aluminium glass door has been designed keeping in mind standard hardware available including concealed or open door closer, dead locks, mortise lock and handles, while GD02S aluminium glass door can be used with soft closing sliding channel.

Technical Data

Main Lock Stile profile 75 x 40.5 mm
Hinge stile and rails 91/80 x 38.5 mm
for single glass 8mm - 10mm
All components are raw mill finish and can be powder coated in any powder coat color or anodized

GREENPRO certified 6063 aluminium alloy, 100% recycled aluminium - 10% precosumer & 90% post-consumer







https://iqubx.com/aluminium-door-frame/

50 x 23

POWDER COAT / ANODIZE



IQUBX Modular Aluminium Door frame with rebate, multi-purpose application, DF01

This is a versatile and multipurpose door frame. This Door frame design can be used with all modular aluminium glass partition system and demountable partition systems, as well as in gypsum partition, masonry Walls etc. This can ensure uniformity of detail and aesthetics on site.

It is recommended for use with IQUBX GP2510, GP2512, GP2512D and WP01P. This door frame can be used with all type of doors including frameless glass doors, Aluminium stile door, wooden doors etc.

The unique door frame design idea has integrated main body and rebate profile, so that it can be used as an independent door frame, while it is sleek enough to be used with glass and solid partition systems. This door frame details has inbuilt double slots for fixing of components of the door frame with the help of brackets, making a strong mitered joint.

This design has also the advantage that it can be fixed post-construction of masonry walls and partition with help of expansion bolts and screws. Therefore, it is very easy to uninstall the complete frame without damaging the fenestration

The frame has double door seal for superior acoustic insulation

Due to the door frame details with 2 numbers 4 mm grooves on each side, there is no need for door frame architrave trims

Technical Data

50 x 23 mm

rebate of 11 mm

Double grooves of 4 mm

Double rubber seal for superior acoustic insulation Can be used with glass partitions, demountable, gypsum or wood partitions or masonry walls too

All components are raw mill finish and can be powder coated in any powder coat color or anodized

GREENPRO certified

6063 aluminium alloy, 100% recycled aluminium - 10% precosumer & 90% post-consumer

